

Product Name:	CRT-LRP-HC-UCBI-0404G
Description:	<p>Undercounter Controlled Room Temperature Cabinet, Built-In 4.6 Cu. Ft. Capacity One glass swing door, right hinged* Microprocessor temperature controller Digital temperature display Audible and visual high and low temperature alarms Remote alarm contacts 2 probes; 1 in air and 1 in sample bottle Adjustable operating temperature range: 68°F–77°F (20°C – 25°C) Temperature monitor device (TMD) complied with the current CDC guidelines, with 3 years certification of calibration, “buffered” probe in the product simulated solution, min/max memory. F/C switchable, field installable, and visual & audible temp alarm. Three shelves (two adjustable/one fixed) with guard rail on back to prevent product from pushing against back wall Back wall evaporator cover Vaccine storage power cord warning label Forced draft circulation Keyed door lock Magnetic door gasket for positive seal Leveling legs LED interior light Probe access port (3/8") Powder coat exterior High density urethane foam cabinet and door insulation HFC-free refrigerant (R600a), foam insulation and packaging Two year parts and labor warranty, plus an additional three year compressor parts only warranty Pyxis®, Omnicell® and AcuDose RX® compatible Exterior dimensions: 23 ¾ "W x 25 ½" D x 33 3/8 "H Cycle defrost 115V, 60 Hz, 1.74 Amps, 1/8 HP UL/C-UL listed Shipping weight: 150 lbs. *This product is available left hinged, product number CRT-ABT-HC-UCBI-0404G-LH</p>