

Product Name:	CRT-LRP-HC-S26G
Description:	<p>Upright Controlled Room Temperature Cabinet, Glass Door  26 Cu. Ft. Capacity  One swing glass door, self-closing (energy efficient, double pane vacuum insulated), right hinged, not reversible  Microprocessor temperature controller  Digital temperature display  Audible and visual high and low temperature alarms  Remote alarm contacts  Adjustable operating temperature range: 68°F–77°F (20°C – 25°C)  Temperature monitor device (TMD) complies with the current CDC guidelines, with 3 years certification of calibration, “buffered” probe in the product simulated solution, min/max memory. F/C switchable, field installable, and visual &amp; audible temp alarm  2 probes; 1 in air and 1 in sample bottle  Four adjustable shelves  Vaccine storage power cord warning label  Forced draft air circulation  Keyed door lock  Magnetic door gasket for positive seal  Heavy duty door handle  Swivel Casters (3”)  LED interior lights are safety shielded and switch controlled  Probe access port (<math>\frac{3}{8}</math>”)  Powder coated steel white interior and exterior  High density urethane foam cabinet insulation  Hydrocarbon, natural refrigerant (R290)  One year parts and labor warranty, plus an additional four year compressor parts warranty  Exterior dimensions: 28 <math>\frac{3}{8}</math>” W x 36 <math>\frac{1}{2}</math>” D x 81 <math>\frac{3}{4}</math>” H with casters; 78 <math>\frac{1}{4}</math>” H without casters  Cycle defrost  115V, 60 Hz, 3 Amps, 1/5 HP  ETL listed  Shipping weight: 355 lbs.</p>