

Product Name:	LRP-HC-33C
Description:	<p>Plus Series Glass Door Chromatography Refrigerator  33 Cu. Ft. capacity  Two sliding glass doors, self-closing (energy efficient, double pane vacuum insulated)  Microprocessor Temperature Controller  Adjustable operating temperature range: 1°-10°C  Standard Digital Temperature Display and Alarm Module  Sample simulated digital temperature display; .1° Resolution  Adjustable temperature display in Celsius or Fahrenheit  Audible and visual high/low temperature alarms  Sensor error alarm  Power failure alarm  Resettable 1-point Min/Max History  Remote alarm contacts  Alarm validation (audible, visual, and remote alarm)  Alarm mute with ring back  Eight adjustable shelves (adjustable in ½" increments)  Forced draft air circulation  Keyed door lock  Magnetic door gasket for positive seal  Integrated door handles  LED interior lights are safety shielded and switch controlled  Swivel casters (adds 4" to height)  One GFCI protected duplex electrical outlet  Two 2" access ports with spring loaded self-closing, gasketed metal covers  Probe access port (3/8")  White laminated vinyl exterior  White aluminum liner and stainless steel floor interior  HFC-free refrigerant (R290), foam insulation and packaging  Two year parts and labor warranty, plus an additional three year compressor parts warranty  Exterior dimensions: 41" W x 31 3/8 " D x 82 5/8" H with casters; 78 5/8" H without casters. *Width w/access ports closed; 49" width w/access ports open  Cycle defrost  115V, 60 Hz, 6.3 Amps, 1/3 HP, BTU/HR 5265  UL/C-UL listed  Shipping weight: 413 lbs.  Note: This unit requires two (2) outlets</p>