

Product Name:	LRP-HC-CP-26
Description:	<p>Plus Series Glass Door Chromatography Refrigerator</p> <p>26 Cu. Ft. capacity</p> <p>One swing glass door, self-closing, right hinged, not reversible</p> <p>Microprocessor Temperature Controller</p> <p>Adjustable operating temperature range: 1°-10°C</p> <p>Digital Temperature Display and Alarm Module</p> <p>Sample simulated digital temperature display; .1° Resolution</p> <p>Adjustable temperature display in Celsius or Fahrenheit</p> <p>Audible and visual high/low temperature alarms</p> <p>2 probes; 1 in air and 1 in sample bottle</p> <p>Sensor error alarm</p> <p>Power failure alarm</p> <p>Resettable 1-point Min/Max History</p> <p>Remote alarm contacts</p> <p>Alarm validation (audible, visual, and remote alarm)</p> <p>Alarm mute with ring back</p> <p>Four adjustable shelves (adjustable in ½" increments)</p> <p>Forced draft air circulation</p> <p>Keyed door lock</p> <p>One GFCI protected duplex electrical outlet</p> <p>Two 2" access ports with spring-loaded, self-closing gasketed metal covers</p> <p>Magnetic door gasket for positive seal</p> <p>Heavy duty door handle</p> <p>LED interior lights are safety shielded and switch controlled</p> <p>Swivel Casters (3 ½")</p> <p>Probe access port (3/4")</p> <p>Advanced hydrocarbon detector</p> <p>White powder-coated steel exterior and interior</p> <p>High density urethane foam cabinet insulation</p> <p>Hydrocarbon, natural refrigerant (R290)</p> <p>Two year parts and labor warranty, plus an additional three year compressor parts warranty</p> <p>Exterior dimensions: 29 1/8" W* x 36 ½" D x 81 ¾" H with casters; 78 ¼" H without casters. *Width w/access port closed; 33 ¼" with access port open</p> <p>Cycle defrost</p> <p>115V, 60 Hz, 3 Amps, 1/5 HP</p> <p>ENERGY STAR CERTIFIED</p> <p>ETL listed</p> <p>Shipping weight: 355 lbs. Note: This unit requires two (2) outlets</p>