

Product Name:	LRP-HC-CP-16-TS
Description:	<p>TempLog Plus Series Glass Door Chromatography Refrigerator  16 Cu. Ft. capacity  One swing glass door, self-closing, right hinged, not reversible  Microprocessor temperature controller  Adjustable operating temperature range: 1°C - 10°C  Touch Screen Digital Temperature Display and Alarm Module  Password-protected control panel  Sample simulated digital temperature display; .1° Resolution, adjustable temperature display in Celsius or Fahrenheit  Active temperature scale bar display  Resettable 1-point min/max history and digital 24-hour temperature chart  Temperature data logging  USB port for data transfer and software updates  Real-time operational display clock  4-20mA output  Electronic troubleshooting guide  Electronic QR Code to access Owner's Manual &amp; technical support contact info  Adjustable alarm volume  Audible and visual high/low temperature alarms  2 probes; 1 in air and 1 in sample bottle  Sensor error alarm, power failure alarm, door ajar alarm, low battery alarm  Operation indicator  Alarm validation (audible, visual, and remote alarm) and alarm mute with ring back Remote alarm contacts  Three adjustable shelves (adjustable in ½" increments)  Forced draft air circulation  Keyed door lock  One GFCI protected duplex electrical outlet  Two 2" access ports with spring-loaded, self-closing gasketed metal covers  Magnetic door gasket for positive seal  Heavy duty door handle  LED interior lights are safety shielded and switch controlled  Swivel Casters (3 ½")  Probe access port (3/4")  Advanced hydrocarbon detector  White powder-coated steel exterior and interior  High density urethane foam cabinet insulation  Hydrocarbon, natural refrigerant (R290)  Three year parts and labor warranty, plus an additional two year compressor parts warranty  Exterior dimensions: 26 1/2" W* x 29 3/4" D x 79" H with casters; 75 ½" H without casters. *Width w/access ports closed; 34 1/2" width w/access ports open  Cycle defrost  115V, 60 Hz, 3 Amps, 1/5 HP  ENERGY STAR CERTIFIED  ETL listed  Shipping weight: 283 lbs. Note: This unit requires two (2) outlets</p>