Description: Plus Series Undercounter Built-In Refrigerator 2.5 Cu. Ft. Capacity One solid swing door, right hinged Microprocessor temperature controller Adjustable operating temperature range: 1°C – 10°C Digital temperature display Audible and visual high and low temperature alarms 2 probes; 1 in air and 1 in sample bottle Remote alarm contacts Four adjustable shelves (two large, two small) with guard rail on back to prevent product from being pushed against the back wall Back wall evaporator cover		Product Name:	LRP-HC-UCBI-0204
<ul> <li>2.5 Cu. Ft. Capacity</li> <li>One solid swing door, right hinged</li> <li>Microprocessor temperature controller</li> <li>Adjustable operating temperature range: 1°C – 10°C</li> <li>Digital temperature display</li> <li>Audible and visual high and low temperature alarms</li> <li>2 probes; 1 in air and 1 in sample bottle</li> <li>Remote alarm contacts</li> <li>Four adjustable shelves (two large, two small) with guard rail on back to prevent product from being pushed against the back wall Back wall evaporator cover</li> </ul>	ľ		
Self-closing door Keyed door lock Magnetic door gasket for positive seal Leveling legs Probe access port (3/8") Powder coat exterior High density urethane foam cabinet and door insulation HFC-free refrigerant (R600a), foam insulation and packaging Two year parts and labor warranty, plus an additional three year compressor parts only warranty Pyxis <sup>®</sup> , Omnicell <sup>®</sup> and AcuDose RX <sup>®</sup> compatible Exterior dimensions: 17 <sup>3</sup> / <sub>4</sub> "W x 22 3/4"D x 30 3/4"H Cycle defrost 115V, 60 Hz, .90 Amps, 1/8 HP Energy Consumption 0.58 kWh/day ADA compliant UL/C-UL listed Shipping weight: 85 lbs.		Description:	<ul> <li>2.5 Cu. Ft. Capacity</li> <li>One solid swing door, right hinged</li> <li>Microprocessor temperature controller</li> <li>Adjustable operating temperature range: 1°C – 10°C</li> <li>Digital temperature display</li> <li>Audible and visual high and low temperature alarms</li> <li>2 probes; 1 in air and 1 in sample bottle</li> <li>Remote alarm contacts</li> <li>Four adjustable shelves (two large, two small) with guard rail on back to prevent product from being pushed against the back wall</li> <li>Back wall evaporator cover</li> <li>Forced draft circulation</li> <li>Self-closing door</li> <li>Keyed door lock</li> <li>Magnetic door gasket for positive seal</li> <li>Leveling legs</li> <li>Probe access port (3/8")</li> <li>Powder coat exterior</li> <li>High density urethane foam cabinet and door insulation</li> <li>HFC-free refrigerant (R600a), foam insulation and packaging</li> <li>Two year parts and labor warranty, plus an additional three year compressor parts only warranty</li> <li>Pyxis®, Omnicell® and AcuDose RX® compatible</li> <li>Exterior dimensions: 17 ¾ "W x 22 3/4"D x 30 3/4"H</li> <li>Cycle defrost</li> <li>115V, 60 Hz, .90 Amps, 1/8 HP</li> <li>Energy Consumption 0.58 kWh/day</li> <li>ADA compliant</li> <li>UL/C-UL listed</li> </ul>