pLog Plus Series Flammable Storage Freezer Cu. Ft. capacity solid swing door, right hinged, not reversible roprocessor temperature controller ustable operating temperature Pisplay and Alarm Module sword-protected control panel rople simulated digital temperature display; .1° Resolution, adjustable perature display in Celsius or Fahrenheit ve temperature scale bar display tettable 1-point min/max history tal 24-hour temperature chart roperature data logging 8 port for data transfer and software updates li-time operational display clock DMA output stronic troubleshooting guide stronic QR Code to access Owner's Manual & technical support contact transion ustable alarm volume lible and visual high/low temperature alarms sor error alarm ver failure alarm or ajar alarm ver battery alarm retation indicator m validation (audible, visual, and remote alarm) m mute with ring back note alarm contacts or fixed shelves ed door lock genetic door gasket for positive seal nless steel door handle eling legs probe access port (3/8") te textured cabinet and door or density urethane foam cabinet and door insulation -free refrigerant (R404a), foam insulation and packaging se year parts and labor warranty rior dimensions: 35 ¾"W x 38"D x 78 ½"H hual defrost V, 60 Hz, 6 Amps, 1/3 HP C-ULL listed s meet NFPA guidelines 45 and 70
rous distribute the first state of the first state