

Product Name:	LRP-HC-33
Description:	<p>Plus Series Glass Door Laboratory Refrigerator</p> <p>33 Cu. Ft. capacity</p> <p>Two sliding glass doors, self-closing (energy efficient, double pane vacuum insulated)</p> <p>Microprocessor Temperature Controller</p> <p>Adjustable operating temperature range: 1°-10°C</p> <p>Standard Digital Temperature Display and Alarm Module with battery back-up to support temperature monitoring and alarms</p> <p>Sample simulated digital temperature display; .1° Resolution</p> <p>Adjustable temperature display in Celsius or Fahrenheit</p> <p>Audible and visual high/low temperature alarms</p> <p>Sensor error alarm</p> <p>Power failure alarm</p> <p>Resettable 1-point Min/Max History</p> <p>Remote alarm contacts</p> <p>Alarm validation (audible, visual, and remote alarm)</p> <p>Alarm mute with ring back</p> <p>Eight adjustable shelves (adjustable in ½" increments)</p> <p>Forced draft air circulation</p> <p>Keyed door lock</p> <p>Magnetic door gasket for positive seal</p> <p>Integrated door handles</p> <p>LED interior lights are safety shielded and switch controlled</p> <p>Swivel casters (adds 4" to height)</p> <p>Probe access port (3/8")</p> <p>White laminated vinyl exterior</p> <p>White aluminum liner and stainless steel floor interior</p> <p>HFC-free refrigerant (R290), foam insulation and packaging</p> <p>Two year parts and labor warranty, plus an additional three year compressor parts warranty</p> <p>Exterior dimensions: 39 ½"W x 30 5/8" D x 82 5/8" H with casters; 78 5/8" H without casters</p> <p>Cycle defrost</p> <p>115V, 60 Hz, 6.3 Amps, 1/3 HP, BTU/HR 5265</p> <p>UL/C-UL listed</p> <p>Shipping weight: 411 lbs.</p>