Description: Basic Series Solid Door Laboratory Refrigerator 23 Cu. Ft. capacity One swing solid door, self-closing, right hinged, not reversible Microprocessor temperature controller Digital temperature display Audible and visual high and low temperature alarms 2 probes; 1 in air and 1 in sample bottle Remote alarm contacts Adjustable operating temperature range: 1°C – 10°C Keyed door lock Magnetic door gasket for positive seal Heavy duty door handle Four adjustable shelves (adjustable in ½" increments) Forced draft air circulation LED interior lights are safety shielded and switch controlled Swivel Casters (3 ½") Probe access port (¾") White powder-coated steel exterior and interior Hydrocarbon, natural refrigerant (R290) One year parts and labor warranty, plus an additional four year compressor parts warranty Exterior dimensions: 26 ¾" W x 34 ¾" D x 81 ¾" H with casters; 78 ¼" H without casters Cycle defrost	Product Name:	LRP-HC-SLB-23
23 Cu. Ft. capacity One swing solid door, self-closing, right hinged, not reversible Microprocessor temperature controller Digital temperature display Audible and visual high and low temperature alarms 2 probes; 1 in air and 1 in sample bottle Remote alarm contacts Adjustable operating temperature range: 1°C – 10°C Keyed door lock Magnetic door gasket for positive seal Heavy duty door handle Four adjustable shelves (adjustable in ½" increments) Forced draft air circulation LED interior lights are safety shielded and switch controlled Swivel Casters (3 ½") Probe access port (%") White powder-coated steel exterior and interior Hydrocarbon, natural refrigerant (R290) One year parts and labor warranty, plus an additional four year compressor parts warranty Exterior dimensions: 26 ½" W x 34 ¾" D x 81 ¾" H with casters; 78 ¼" H without casters		
115V, 60 Hz, 3 Amps, 1/5 HP ENERGY STAR CERTIFIED ETL listed Shipping weight: 250 lbs.	Description:	23 Cu. Ft. capacity One swing solid door, self-closing, right hinged, not reversible Microprocessor temperature controller Digital temperature display Audible and visual high and low temperature alarms 2 probes; 1 in air and 1 in sample bottle Remote alarm contacts Adjustable operating temperature range: 1°C – 10°C Keyed door lock Magnetic door gasket for positive seal Heavy duty door handle Four adjustable shelves (adjustable in ½" increments) Forced draft air circulation LED interior lights are safety shielded and switch controlled Swivel Casters (3 ½") Probe access port (¾") White powder-coated steel exterior and interior Hydrocarbon, natural refrigerant (R290) One year parts and labor warranty, plus an additional four year compressor parts warranty Exterior dimensions: 26 ½" W x 34 ¾" D x 81 ¾" H with casters; 78 ¼" H without casters Cycle defrost 115V, 60 Hz, 3 Amps, 1/5 HP ENERGY STAR CERTIFIED ETL listed