

Product Name:	LRP-HC-23S
Description:	<p>Plus Series Solid Door Laboratory Refrigerator 23 Cu. Ft. capacity One swing solid door, self-closing, right hinged, not reversible Microprocessor Temperature Controller Adjustable operating temperature range: 1°-10°C Standard Digital Temperature Display and Alarm Module with battery back-up to support temperature monitoring and alarms Sample simulated digital temperature display; .1° Resolution Adjustable temperature display in Celsius or Fahrenheit Audible and visual high/low temperature alarms Sensor error alarm Power failure alarm Resettable 1-point Min/Max History 2 probes; 1 in air and 1 in sample bottle Remote alarm contacts Alarm validation (audible, visual, and remote alarm) Alarm mute with ring back Four adjustable shelves (adjustable in ½" increments) Forced draft air circulation Keyed door lock Magnetic door gasket for positive seal Heavy duty door handle LED interior lights are safety shielded and switch controlled Swivel Casters (3 ½") probe access port (¾") White powder-coated steel exterior and interior Hydrocarbon, natural refrigerant (R290) Two year parts and labor warranty, plus an additional three compressor parts warranty Exterior dimensions: 26 7/8" W x 34 3/4" D x 81 3/4" H with casters; 78 1/4" H without casters Cycle defrost 115V, 60 Hz, 3 Amps, 1/5 HP ETL listed Shipping weight: 250 lbs.</p>