

Product Name:	LRP-HC-72S
Description:	<p>Plus Series Solid Door Laboratory Refrigerator  72 Cu. Ft. capacity  Three swing solid doors, self-closing, right hinged, not reversible  Microprocessor Temperature Controller  Adjustable operating temperature range: 1°-10°C  Standard Digital Temperature Display and Alarm Module with battery back-up to support temperature monitoring and alarms  Sample simulated digital temperature display; .1° Resolution  Adjustable temperature display in Celsius or Fahrenheit  Audible and visual high/low temperature alarms  Sensor error alarm  Power failure alarm  Resettable 1-point Min/Max History  2 probes; 1 in air and 1 in sample bottle  Remote alarm contacts  Alarm validation (audible, visual, and remote alarm)  Alarm mute with ring back  Twelve adjustable shelves (adjustable in ½" increments)  Forced draft air circulation  Keyed door lock  Magnetic door gasket for positive seal  Heavy duty door handle  LED interior lights are safety shielded and switch controlled  Swivel Casters (3 ½")  probe access port (¾")  White powder-coated steel exterior and interior  Hydrocarbon, natural refrigerant (R290)  Two year parts and labor warranty, plus an additional three compressor parts warranty  Exterior dimensions: 81" W x 34" D x 81 ¾" H with casters; 78 ¼" H without casters  Cycle defrost  115V, 60 Hz, 7.5 Amps, 1/2 HP  ETL listed  Shipping weight: 600 lbs.</p>