

Product Name:	LRP-HCPP-72
Description:	<p>Plus Series Stainless Steel Laboratory Refrigerator 72 Cu. Ft. Capacity Three swing stainless steel doors Multi-Point temperature mapping via NIST traceable data acquisition, 15 probes in air and 3 probes in sample solution for 360 minutes with temperature readings every 60 seconds Microprocessor Temperature Controller Adjustable operating temperature range: 1°C - 10°C Digital Temperature Display and Alarm Module with battery back-up to support temperature monitoring and alarms Sample simulated digital temperature display; .1° Resolution Adjustable temperature display in Celsius or Fahrenheit Audible and visual high/low temperature alarms Sensor error alarm Power failure alarm Resettable 1-point min/max history Remote alarm contacts Alarm validation (audible, visual, and remote alarm) Alarm mute with ring back Nine shelves (adjustable in ½" increments) Forced draft air circulation Keyed door lock Magnetic door gasket for positive seal Heavy duty door handles Swivel casters (adds 5" to height) Interior light Probe access port (3/8") 300 Series stainless steel interior/exterior High density urethane foam cabinet insulation HFC-free refrigerant (R290), foam insulation and packaging Two year parts and labor warranty, plus an additional three year compressor parts warranty Exterior dimensions: 78 1/8"W x 30 3/4"D x 83 5/8"H with casters; 78 5/8"H without casters Cycle defrost 115V, 60 Hz, 6.9 Amps, 3/4 HP, BTU/HR 7315 UL/C-UL listed Shipping weight: 650 lbs.</p>