

Product Name:	LRP-HC-UCBI-0420A-LH
Description:	<p>Plus Series Undercounter Auto Defrost Freezer Built-In-LEFT HINGED</p> <p>4.2 Cu. Ft. Capacity</p> <p>One solid swing door, left hinged</p> <p>Microprocessor temperature controller</p> <p>Digital temperature display</p> <p>Audible and visual high and low temperature alarms</p> <p>2 probes; 1 in air and 1 in glycol bottle</p> <p>Adjustable operating temperature range: -15°C – -25°C</p> <p>Auto defrost cycle every 6 hours, max air temp in empty freezer: +4.9°C; max air temp in loaded freezer: +0.6°C. Max sample temp in empty freezer: -9.1°C; max sample temp in loaded freezer: -11.2°C</p> <p>Three adjustable shelves with guard rail on back to prevent product from being pushed against the back wall</p> <p>Back wall evaporator cover</p> <p>Keyed door lock</p> <p>Heavy duty door handle</p> <p>Magnetic door gasket for positive seal</p> <p>Leveling legs</p> <p>Probe access port (3/8")</p> <p>Powder coat exterior</p> <p>High density urethane foam cabinet and door insulation</p> <p>HFC-free refrigerant (R600a), foam insulation and packaging</p> <p>Two year parts and labor warranty</p> <p>Pyxis®, Omnicell® and AcuDose RX® compatible</p> <p>Exterior dimensions: 23 3/4" W x 24 1/2" D x 33 1/8"H</p> <p>Auto defrost</p> <p>115V, 60 Hz, 1.8 Amps 1/8 HP</p> <p>UL/C-UL listed</p> <p>Shipping weight: 143 lbs.</p> <p>DISCLAIMER: Auto defrost freezers incorporate an electric heater installed on the evaporator that assist in the removal of the frost and ice. Although the heater helps speed up the frost and ice removal, it can raise the temperatures within the freezer.</p>