PH-LRP-HC-S33G
Basic Series Pharmacy/Vaccine Sliding Glass Door Refrigerator 33 Cu. Ft. Capacity Two sliding glass doors, self-closing (energy efficient, double pane vacuum insulated) Microprocessor temperature controller Digital temperature display Audible and visual high and low temperature alarms Remote alarm contacts 2 probes; 1 in air and 1 in sample bottle Adjustable operating temperature range: $36^{\circ}F - 46^{\circ}F$ ( $2^{\circ}C - 8^{\circ}C$ ) Temperature monitor device (TMD) complies with the current CDC guidelines, with 3 years certification of calibration, "buffered" probe in the product simulated solution, min/max memory. F/C switchable, field installable, and visual & audible temp alarm Eight adjustable shelves (adjustable in $\frac{1}{2}$ " increments) Vaccine storage power cord warning label Forced draft air circulation Keyed door lock Magnetic door gasket for positive seal Integrated door handles Swivel Casters (3 $\frac{1}{2}$ ") LED interior lights are safety shielded and switch controlled Probe access port ( $\frac{3}{7}$ ") Powder coated steel white interior and exterior High density urethane foam cabinet insulation Hydrocarbon, natural refrigerant (R290) Pharmacy refrigerator/freezer toolkit and temperature logs One year parts and labor warranty, plus an additional four year compressor parts warranty Exterior dimensions: 39 $\frac{5}{7}$ " W x 33 $\frac{1}{4}$ " D x 81 $\frac{3}{4}$ " H with casters; 78
14" H without casters Cycle defrost 115V, 60 Hz, 4.5 Amps, ¼ HP ETL listed Shipping weight: 419 lbs.