	PH-LRP-HC-S47G
Description:	Basic Series Pharmacy/Vaccine Sliding Glass Door Refrigerator 47 Cu. Ft. Capacity Two sliding glass doors, self-closing (energy efficient, double pane vacuum insulated) Microprocessor temperature controller Digital temperature display Audible and visual high and low temperature alarms Remote alarm contacts 2 probes; 1 in air and 1 in sample bottle Adjustable operating temperature range: 36°F – 46°F (2°C – 8°C) Temperature monitor device (TMD) complies with the current CDC guidelines, with 3 years certification of calibration, "buffered" probe in the product simulated solution, min/max memory. F/C switchable, field installable, and visual & audible temp alarm Eight adjustable shelves (adjustable in ½" increments) Vaccine storage power cord warning label Forced draft air circulation Keyed door lock Magnetic door gasket for positive seal Integrated door handles Swivel Casters (3 ½") LED interior lights are safety shielded and switch controlled Probe access port (¾") Powder coated steel white interior and exterior High density urethane foam cabinet insulation Hydrocarbon, natural refrigerants (R290) Pharmacy refrigerator/freezer toolkit and temperature logs One year parts and labor warranty, plus an additional four year compressor parts warranty Exterior dimensions: 54 ½" W x 33 ¼" D x 81 ¾" H with casters; 78
	Lexiendr dimensions: 54 % W X 33 % D X 81 % H with casters; 78 1/4" H without casters Cycle defrost 115V, 60 Hz, 4.5 Amps. 1/4 HP ETL listed Shipping weight: 508 lbs.