Product Name:	PH-LRP-HC-S69G
Description:	Basic Series Pharmacy/Vaccine Glass Door Refrigerator 69 Cu. Ft. Capacity Three sliding glass doors, self-closing (energy efficient, double pane vacuum insulated) Microprocessor temperature controller Digital temperature display Audible and visual high and low temperature alarms Remote alarm contacts 2 probes; 1 in air and 1 in sample bottle Adjustable operating temperature range: 36°F – 46°F (2°C – 8°C) Temperature monitor device (TMD) complies with the current CDC guidelines, with 3 years certification of calibration, "buffered" probe in the product simulated solution, min/max memory. F/C switchable, field installable, and visual & audible temp alarm Twelve adjustable shelves (adjustable in ½" increments) Vaccine storage power cord warning label Forced draft air circulation Keyed door lock Magnetic door gasket for positive seal Integrated door handles Swivel Casters (3 ½") LED interior lights are safety shielded and switch controlled Probe access port (¾") Powder coated steel white interior and exterior High density urethane foam cabinet insulation Hydrocarbon, natural refrigerant (R290) Pharmacy refrigerator/freezer toolkit and temperature logs
	Probe access port (%") Powder coated steel white interior and exterior High density urethane foam cabinet insulation Hydrocarbon, natural refrigerant (R290)
	One year parts and labor warranty, plus an additional four year compressor parts warranty Exterior dimensions: 81" W x 33 1/4" D x 81 3/4" H with casters; 78 1/4" H without casters Cycle defrost
	115V, 60 Hz, 7.5 Amps, 1/2 HP ETL listed Shipping weight: 738 lbs.