

Product Name:	PH-LRP-HC-S49S
Description:	<p>Basic Series Pharmacy/Vaccine Solid Door Refrigerator</p> <p>49 Cu. Ft. capacity</p> <p>Two swing solid doors, self-closing, right hinged, not reversible</p> <p>Microprocessor temperature controller</p> <p>Digital temperature display</p> <p>Audible and visual high and low temperature alarms</p> <p>Remote alarm contacts</p> <p>2 probes; 1 in air and 1 in sample bottle</p> <p>Adjustable operating temperature range: 36°F – 46°F (2°C – 8°C)</p> <p>Temperature monitor device (TMD) complies with the current CDC guidelines, with 3 years certification of calibration, “buffered” probe in the product simulated solution, min/max memory. F/C switchable, field installable, and visual &amp; audible temp alarm</p> <p>Keyed door locks</p> <p>Magnetic door gasket for positive seal</p> <p>Eight adjustable shelves (adjustable in ½” increments)</p> <p>Vaccine storage power cord warning label</p> <p>Forced draft air circulation</p> <p>Heavy duty door handles</p> <p>LED interior lights are safety shielded and switch controlled</p> <p>Swivel Casters (3 ½”)</p> <p>probe access port (⅜”)</p> <p>White powder-coated steel exterior and interior</p> <p>Hydrocarbon, natural refrigerant (R290)</p> <p>Pharmacy refrigerator/freezer toolkit and temperature logs</p> <p>One year parts and labor warranty, plus an additional four year compressor parts warranty</p> <p>Exterior dimensions: 54” W x 34 ¾” D x 81 ¾” H with casters; 78 ¼” H without casters</p> <p>Cycle defrost</p> <p>115V, 60 Hz, 4.5 Amps, 1/4 HP</p> <p>ENERGY STAR CERTIFIED</p> <p>ETL listed</p> <p>Shipping weight: 446 lbs.</p>