Product Name:	PH-LRP-HC-SSP-49G
Description:	49 Cu. Ft. capacity Two swing glass doors, self-closing, not reversible 8 ea. adjustable shelves Digital display microprocessor temperature controller Adjustable operating temperature: 36°F to 46°F) Temperature Monitor Device - complies with the current CDC guidelines, 3 years certification of calibration, "buffered" probe in the product simulated solution, min/max memory, °F/°C switchable, field installable, and visual & audible temperature alarms 2 probes; 1 in air and 1 in sample bottle Sensor error alarm Continuous product (simulated) temperature display Remote alarm contacts Forced draft air circulation Keyed door locks Magnetic door gaskets for positive seal Integrated door handle LED interior lights are safety shielded and switch controlled Probe access port (3/4") Stainless steel exterior White-powder coated aluminum interior with 304 stainless steel floor Easily cleaned smooth interior Hydrocarbon natural refrigerant (R290) 2 year parts and labor warranty, plus an additional 3 year compressor parts warranty 4 swivel casters (5 3/4") Exterior dimensions: 54" W x 35 ¾" D x 83 1/4" H with casters; 77 1/2" H without casters Cycle defrost 115V, 60 Hz, 4.5 Amps, 1/4 HP ETL listed
L	Shipping weight: 557 lbs.