

Product Name:	CRT-LRP-HC-S49G
Description:	Upright Controlled Room Temperature Cabinet, Glass Door 49 Cu. Ft. Capacity Two swing glass doors, self-closing (energy efficient, double pane vacuum insulated) Microprocessor temperature controller Digital temperature display Audible and visual high and low temperature alarms Remote alarm contacts Adjustable operating temperature range: 68°F–77°F (20°C – 25°C) Calibrated using a NIST traceable device, certificate included 2 probes; 1 in air and 1 in sample bottle Eight adjustable shelves Vaccine storage power cord warning label Forced draft air circulation Keyed door lock Magnetic door gasket for positive seal Heavy duty door handles Swivel Casters (3") LED interior lights are safety shielded and switch controlled Probe access port ($\frac{3}{8}$") Powder coated steel white interior and exterior High density urethane foam cabinet insulation Hydrocarbon, natural refrigerant (R290) One year parts and labor warranty, plus an additional four year compressor parts warranty Exterior dimensions: 54" W x 34 $\frac{3}{4}$" D x 81 $\frac{3}{4}$" H with casters; 78 $\frac{1}{4}$" H without casters Cycle defrost 115V, 60 Hz, 4.5 Amps, 1/4 HP ENERGY STAR CERTIFIED ETL listed Shipping weight: 538 lbs.