Product Name	CRT-LRP-HC-UCBI-0204
. Toddot Harrio.	- C.
Description:	Undercounter Controlled Room Temperature Cabinet, Built-In 2.5 Cu. Ft. Capacity One solid swing door, right hinged Microprocessor temperature controller Digital temperature display Adjustable operating temperature range: 36°F – 46°F (2°C – 8°C) Calibrated using a NIST traceable device, certificate included Remote alarm contacts 2 probes; 1 in air and 1 in sample bottle Four adjustable shelves (two large, two small) with guard rail on back to prevent product from being pushed against the back wall Back wall evaporator cover Vaccine storage power cord warning label Forced draft circulation Self-closing door Keyed door lock Magnetic door gasket for positive seal Leveling legs LED light Probe access port (3/8") Powder coat exterior High density urethane foam cabinet and door insulation HFC-free refrigerant (R600a), foam insulation and packaging Two year parts and labor warranty, plus an additional three year compressor parts only warranty Pyxis®, Omnicell® and AcuDose RX® compatible Exterior dimensions: 17 3/4"W x 22 3/4"D x 30 3/4"H Cycle defrost 115V, 60 Hz, .90 Amps, 1/8 HP ADA compliant UL/C-UL listed Shipping weight: 85 lbs.