Description: PH-LRP-HC-UCBI-0404SS Description: Plus Series Pharmacy/Vaccine Undercounter Refrigerator Built-In 4.5 Cu. Ft. Capacity One solid stainless steel swing door, right hinged* Microprocessor temperature controller Digital temperature display Audible and visual high and low temperature alarms Remote alarm contacts Adjustable operating temperature range: 36°F – 46°F (2°C – 8°C) Calibrated using a NIST traceable device, certificate included 2 probes; 1 in air and 1 in sample bottle Three shelves (two adjustable/one fixed) with guard rail on back to prevent product from pushing against back wall Back wall evaporator cover Forced draft circulation Vaccine storage power cord warning label Recessed door handle Keyed door lock Magnetic door gasket for positive seal Leveling legs Probe access port (3/8") Stainless steel exterior High density urethane foam cabinet and door insulation HFC-free refrigerant (R600a), foam insulation and packaging Pharmacy refrigerator/freezer toolkit and temperature logs Two year parts and labor warranty, plus an additional three year compressor parts only warranty Pyxis®, Omnicell® and AcuDose RX® compatible Exterior dimensions: 23 ¾"W x 24 ½"D x 33 ¾"H Cycle defrost 115V, 60 Hz, 1.74 Amps, 1/8 HP UL/C-UL listed ENERGY STAR CERTIFIED Shipping weight: 135 lbs. *This product is available left hinged, product number PH-LRP-HC-UCBI-0404SS-LH	Dan de et Marana	DILL DD LIG LIGDI 040400
4.5 Cu. Ft. Capacity One solid stainless steel swing door, right hinged* Microprocessor temperature controller Digital temperature display Audible and visual high and low temperature alarms Remote alarm contacts Adjustable operating temperature range: 36°F – 46°F (2°C – 8°C) Calibrated using a NIST traceable device, certificate included 2 probes; 1 in air and 1 in sample bottle Three shelves (two adjustable/one fixed) with guard rail on back to prevent product from pushing against back wall Back wall evaporator cover Forced draft circulation Vaccine storage power cord warning label Recessed door handle Keyed door lock Magnetic door gasket for positive seal Leveling legs Probe access port (3/8") Stainless steel exterior High density urethane foam cabinet and door insulation HFC-free refrigerant (R600a), foam insulation and packaging Pharmacy refrigerator/freezer toolkit and temperature logs Two year parts and labor warranty, plus an additional three year compressor parts only warranty Pyxis®, Omnicel® and AcuDose RX® compatible Exterior dimensions: 23 ¾"W x 24 ½"D x 33 ¾"H Cycle defrost 115V, 60 Hz, 1.74 Amps, 1/8 HP UL/C-UL listed ENERGY STAR CERTIFIED Shipping weight: 135 lbs. *This product is available left hinged, product number	Product Name:	PH-LRP-HC-UCBI-040455
This product is available left hinged, product number		4.5 Cu. Ft. Capacity One solid stainless steel swing door, right hinged Microprocessor temperature controller Digital temperature display Audible and visual high and low temperature alarms Remote alarm contacts Adjustable operating temperature range: 36°F – 46°F (2°C – 8°C) Calibrated using a NIST traceable device, certificate included 2 probes; 1 in air and 1 in sample bottle Three shelves (two adjustable/one fixed) with guard rail on back to prevent product from pushing against back wall Back wall evaporator cover Forced draft circulation Vaccine storage power cord warning label Recessed door handle Keyed door lock Magnetic door gasket for positive seal Leveling legs Probe access port (3/8") Stainless steel exterior High density urethane foam cabinet and door insulation HFC-free refrigerant (R600a), foam insulation and packaging Pharmacy refrigerator/freezer toolkit and temperature logs Two year parts and labor warranty, plus an additional three year compressor parts only warranty Pyxis®, Omnicell® and AcuDose RX® compatible Exterior dimensions: 23 ¾"W x 24 ½"D x 33 ¾"H Cycle defrost 115V, 60 Hz, 1.74 Amps, 1/8 HP UL/C-UL listed ENERGY STAR CERTIFIED
		compressor parts only warranty Pyxis®, Omnicell® and AcuDose RX® compatible Exterior dimensions: 23 ¾"W x 24 ½"D x 33 ¾"H Cycle defrost 115V, 60 Hz, 1.74 Amps, 1/8 HP UL/C-UL listed ENERGY STAR CERTIFIED Shipping weight: 135 lbs. *This product is available left hinged, product number