Description: Plus Series Pharmacy/Vaccine Undercounter Auto Defrost Freezer Built-In-LEFT HINGED 4.2 Cu. Ft. Capacity One solid swing door, left hinged Microprocessor temperature controller Digital temperature display Audible and visual high and low temperature alarms 2 probes; 1 in air and 1 in glycol bottle Adjustable operating temperature range: 5°F13°F (-15°C25°C) Auto defrost cycle every 6 hours, max air temp in empty freezer: +4.34°C; max air temp in loaded freezer: -2.89°C. Max sample temp in empty freezer: -4.76°C; max sample temp in obaded freezer: -9.58°C. Calibrated using a NIST traceable device, certificate included Three adjustable shelves with guard rail on back to prevent product from being pushed against the back wall Back wall evaporator cover Vaccine storage power cord warning label Keyed door lock Heavy duty door handle Magnetic door gasket for positive seal Leveling legs Probe access port (3/8") Powder coat exterior High density urethane foam cabinet and door insulation HFC-free refrigerant (R290), foam insulation and packaging Pharmacy refrigerator/freezer toolkit and temperature logs Two year parts and labor warranty, plus an additional three year compressor parts only warranty Pyxis®, Omnicell® and AcuDose RX® compatible Exterior dimensions: 23 3/4" W x 24 1/2" D x 33 1/8"H Auto defrost 115V, 60 Hz, 1.8 Amps 1/8 HP UL/C-UL listed Shipping weight: 143 lbs. DISCLAIMER: Auto defrost freezers incorporate an electric heater installed on the evaporator that assist in the removal of the frost and ice. Although the heater helps speed up the frost and ice removal, it can raise the temperatures within the freezer.	Product Name:	PH-LRP-HC-UCBI-0420A-LH
Built-In-LEFT HINGED 4.2 Cu. Ft. Capacity One solid swing door, left hinged Microprocessor temperature controller Digital temperature display Audible and visual high and low temperature alarms 2 probes; 1 in air and 1 in glycol bottle Adjustable operating temperature range: 5°F – -13°F (-15°C – -25°C) Auto defrost cycle every 6 hours, max air temp in empty freezer: +4.34°C; max air temp in loaded freezer: -2.89°C. Max sample temp in empty freezer: -4.76°C; max sample temp in loaded freezer: -9.58°C. Calibrated using a NIST traceable device, certificate included Three adjustable shelves with guard rail on back to prevent product from being pushed against the back wall Back wall evaporator cover Vaccine storage power cord warning label Keyed door lock Heavy duty door handle Magnetic door gasket for positive seal Leveling legs Probe access port (3/8") Powder coat exterior High density urethane foam cabinet and door insulation HFC-free refrigerant (R290), foam insulation and packaging Pharmacy refrigerator/freezer toolkit and temperature logs Two year parts and labor warranty, plus an additional three year compressor parts only warranty Pyxis®, Omnicell® and AcuDose RX® compatible Exterior dimensions: 23 3/4" W x 24 1/2" D x 33 1/8"H Auto defrost 115V, 60 Hz, 1.8 Amps 1/8 HP UL/C-UL listed Shipping weight: 143 lbs. DISCLAIMER: Auto defrost freezers incorporate an electric heater installed on the evaporator that assist in the removal of the frost and ice. Although the heater helps speed up the frost and ice removal, it		
1	Description:	Built-In-LEFT HINGED 4.2 Cu. Ft. Capacity One solid swing door, left hinged Microprocessor temperature controller Digital temperature display Audible and visual high and low temperature alarms 2 probes; 1 in air and 1 in glycol bottle Adjustable operating temperature range: 5°F – -13°F (-15°C – -25°C) Auto defrost cycle every 6 hours, max air temp in empty freezer: +4.34°C; max air temp in loaded freezer: -2.89°C. Max sample temp in empty freezer: -4.76°C; max sample temp in loaded freezer: -9.58°C. Calibrated using a NIST traceable device, certificate included Three adjustable shelves with guard rail on back to prevent product from being pushed against the back wall Back wall evaporator cover Vaccine storage power cord warning label Keyed door lock Heavy duty door handle Magnetic door gasket for positive seal Leveling legs Probe access port (3/8") Powder coat exterior High density urethane foam cabinet and door insulation HFC-free refrigerant (R290), foam insulation and packaging Pharmacy refrigerator/freezer toolkit and temperature logs Two year parts and labor warranty, plus an additional three year compressor parts only warranty Pyxis®, Omnicell® and AcuDose RX® compatible Exterior dimensions: 23 3/4" W x 24 1/2" D x 33 1/8"H Auto defrost 115V, 60 Hz, 1.8 Amps 1/8 HP UL/C-UL listed Shipping weight: 143 lbs. DISCLAIMER: Auto defrost freezers incorporate an electric heater installed on the evaporator that assist in the removal of the frost and ice. Although the heater helps speed up the frost and ice removal, it