

Product Name:	PH-LRP-HC-UCFS-0120A-CAD
Description:	Plus Series Pharmacy/Vaccine Countertop Controlled Auto Defrost Freezer Freestanding 1 Cu. Ft. Capacity One solid swing door, right hinged Microprocessor temperature controller Digital temperature display with sample simulated probe Audible and visual high and low temperature alarms Remote alarm contacts Operating temperature range: 5°F – -13°F (-15°C – -25°C) Defrost: Auto defrost cycle every 6 hours: (at Set Point -11°F /-24°C) Max air temp in empty freezer: 5°F (-15°C) Max air temp in loaded freezer: 3°F (-16°C) Max sample temp in empty freezer: 0°F (-18°C) Max sample temp in loaded freezer: -4°F (-20°C) Calibrated using a NIST traceable device, certificate included 2 adjustable shelves Vaccine storage power cord warning label Keyed door lock Magnetic door gasket for positive seal Leveling legs Probe access port (3/8") Powder coat exterior High density urethane foam cabinet and door insulation HFC-free refrigerant (R600a), foam insulation and packaging Pharmacy refrigerator/freezer toolkit and temperature logs Two year parts and labor warranty, plus an additional three year compressor parts only warranty Pyxis®, Omnicell® and AcuDose RX® compatible Exterior dimensions: 23 ¾ "W x 24" D x 20 3/8"H <i>Note: This unit must have 4" clearance on sides and back for adequate ventilation</i> Controlled Auto Defrost, Patented Technology 115V, 60 Hz, 1 Amp, 1/8 HP ENERGY STAR CERTIFIED ADA UL/C-UL Shipping weight: 106 lbs.

compliant
listed