



# 17 Cu. Ft. Ultra Low Temperature Touchscreen Freezer Dual Voltage

Model: LRP-HC-1786-TS



### Description:

Transform your laboratory with these industry-leading ultra-low temperature freezers. Protect your samples with steel-insulated inner doors for ultimate temperature retention down to -86°C. Experience highly efficient variable speed compressors for energy savings and enhanced system performance. Conduct advanced data logging through intuitive touchscreen control—track real-time temperature readings, export data, and capture trends with just a few taps. Dual voltage compatibility ensures installation flexibility, with each unit including both 115V and 230V power cords under a single part number. You can also rest secure knowing your samples are guarded by a full array of alarms—no more surprise temperature excursions. As a finishing touch, you'll benefit from natural hydrocarbon refrigerants for sustainability, energy efficiency, and long-term cost savings. Together, these features are designed to push boundaries and harness the full potential of the modern ULT.

### Additional Product Images



### Description

Storage capacity (cu. ft)	17 Cu. Ft. Capacity
Door	One solid exterior door, right hinged, not reversible; Five insulated inner doors
Shelves	Four adjustable, stainless steel standard, tested to 160 lbs. (optional configurations available)
Box Capacity	Qty. 320 2" boxes (20 UF442 racks)
Mounting	Four heavy duty swivel casters with locks
External probe access	1/2" diameter port; access from back of unit to interior left side
Insulation	Foamed-in-place EPA compliant high density urethane foam
Exterior materials	Powder coated Steel
Insulation	Cabinet is foamed-in-place with EPA compliant high density urethane foam
Interior lighting	Non-applicable



# 17 Cu. Ft. Ultra Low Temperature Touchscreen Freezer Dual Voltage

Model: LRP-HC-1786-TS

Access Control	Key lock on exterior door handle
General warranty	Five (5) year parts and labor warranty
Compressor warranty	Seven (7) years compressor warranty
Product Weight (lbs.)	630
Shipping Weight (lbs.)	725
Exterior Width (in)	37.6"
Exterior Depth (in)	36.3"
Exterior Height (in)	79.6"
Rated Amperage	10A (120V), 6A (240V)
Power Plug/Power Cord	Two detachable cords supplied, min. 8' length: 120V (NEMA 5-15 Plug) and 240V (NEMA 6-15 Plug)
Facility Electrical Requirement	Dual Voltage 110-120V 15A (minimum) or 208-240V AC 15A (minimum)
Agency Listing and Certification	UL/C-UL listed. Certified to UL 60335-2-89 Safety Standard

## Refrigeration System

Vacuum Relief Port:	Includes heated vacuum relief port for pressure equalization reducing wait times between door openings
Average heat rejection (BTU/h):	1602 BTU/h
Energy Consumption (kWh/Day/CUFT)	As low as 0.59 kWh/day/cu.ft.
Adjustable Temperature Range	-86°C to -50°C
Warm-up times:	180+ minutes -80°C to -50°C°
Evaporator:	Cold wall (Natural convection)
Compressor:	Two ea. variable speed hermetic reciprocating
Condenser:	Tube and Fin design, EC fan, easy clean removable filter

## Temp Controller

Controller technology	Microprocessor with color touchscreen (11in) input and display, C° or F°
Battery Backup	12V high capacity battery for controller and touchscreen display: temperature monitoring, alarms, and event logging active
External alarm connection	State switching remote alarm contacts
Digital Communication	4-20mA output for temperature monitoring
Alarms	Audible and Visual Alarms: customizable sounds and volumes; mute with visual persistence; ring-back functionality re-engages audible alarm after pre-set delay if alarm condition persists. Adjustable delays for door, temperature, power loss.



# 17 Cu. Ft. Ultra Low Temperature Touchscreen Freezer Dual Voltage

Model: LRP-HC-1786-TS

Disclaimers	Indoor use only, +18C to +26C (+65F to +78F), <70% RH. Specifications are subject to change. Backup battery maintains display, data logging, and alarms. Cooling capability is not maintained without external generator.
Optional Accessories	Removable storage racks, Precision fit rack system (in place of shelves), storage boxes, Wi-Fi data logger, additional shelves, additional chamber temperature (sample) probe.