

72 Cu. Ft. Premium Laboratory Glass Door Refrigerator

Model: LRP-HC-PL-72



Description:




Premium Lab Refrigerators deliver superior cooling to laboratory environments. Engineered with variable speed compressors (VSCs), these units feature ultra-quiet operation and significant energy savings. VSCs optimize energy consumption by self-adjusting to cooling demands. These compressors also deliver enhanced system performance and provide a longer lifespan than other compressor variations. Enjoy the uniformity and speed of microprocessor temperature control and a full array of alarms to safeguard your products. Unit controllers also come with a battery backup to keep your data safe. Upgrade your laboratory environment with these premium refrigerators and welcome energy savings, noise reduction, smooth operation, and improved system performance to your work environment.

Additional Product Images



Description

Storage capacity (cu. ft)	72
Door	Triple Swing Glass Right and Left Hinged Door(s)
Shelves	Fifteen adjustable shelves with guard rail on back
Drawers	Optional pull-out drawers available
Mounting and Installation	6 preinstalled swivel casters, front casters locking
Interior lighting	Shielded, switched LED lighting, full coverage, balanced spectrum
Airflow Management	Patented Forced Air Technology
External probe access	Rear wall port (3/4" dia.
Insulation	Cabinet is foamed-in-place with EPA compliant high density urethane foam
Exterior materials	White powder coated steel



72 Cu. Ft. Premium Laboratory Glass Door Refrigerator

Model: LRP-HC-PL-72


Access control	Key Lock
General warranty	Two (2) years parts and labor warranty
Compressor warranty	Seven (7) years compressor warranty
Product Weight (lbs)	728
Shipping Weight (lbs)	880
Exterior Width (in)	81
Exterior Depth (in)	36.25
Exterior Height (in)	81.5
Rated Amperage	5 Amps
Power Plug/Power Cord	NEMA 5-15 plug, 8-10 ft typical
Facility Electrical Requirement	110-120V AC: 15 A (minimum)
Agency Listing and Certification	ETL, C-ETL listed and certified to UL471 standard, hydrocarbon refrigerant safety

Performance

Uniformity(Cabinet air)	±0.86
Stability(Cabinet air)	±0.61
Maximum temperature variation (Cabinet air)	±1.15
Stability ² (Simulator ballast)	Non-applicable
Stability ² (Simulator bag)	Non-applicable
Temperature Rise after Short Door Openings	Non-applicable
Recovery after Short Door Openings	Non-applicable
Energy Consumption (KWh/day)	2.01
Average Heat Rejection (BTU/hr)	625
Noise Pressure Level (dBA)	47 or less installed
Pull down time to nominal operating temp	80 min
Compressor	Hermetic, variable speed (VSC). Rated speed range: 1600-4000 rpm
Refrigerant	EPA SNAP compliant, R290
Condenser	Anti-fouling tube and grid design, ultra-quiet multi-speed fan
Evaporator	Fin and tube design, high efficiency fan
Defrost	Cycle optimized, zero energy

Temp Controller

Controller technology	Proportional Integral Derivative (PID) microprocessor with LCD display
Battery Backup	24V high-capacity battery, controller, all alarms active, temperature monitoring DAQ and event logging active on battery backup
Display technology	LCD Display
Digital Communication	RS-485 (MODBUS)
Data Transfer	USB port for data transfer and software updates



72 Cu. Ft. Premium Laboratory Glass Door Refrigerator

Model: LRP-HC-PL-72

Chart Recorder	Non-applicable
Adjustable Temperature Range	1°C to 10°C
External alarm connection	State switching remote alarm contacts
Alarms	Alarm logging (last 100 entries) with Visual and audible indicators: Power failure, Temperature sensor failure, Battery voltage monitor and replacement, High / Low temperature, Door ajar.
Simulator Ballast	Bottle with glass bead thermal media