



Description:



The Basic Series Laboratory Refrigerators are purpose built for scientific and research applications. These units feature a digital microprocessor temperature controller allowing for the precise temperature management necessary for critical samples and supplies. A forced air directional refrigeration system provides superior temperature uniformity and recovery after door openings. Models are ETL Listed. **Models utilize environmentally friendly, natural hydrocarbon (HC) refrigerants (not containing hydrofluorocarbons) vastly reduce global-warming potential (GWP) while meeting new EPA/SNAP mandates and UL, ASHRAE compliance guidelines**

Additional Product Images



Details

- 4 full adjustable shelves / 1 half adjustable shelf

- Keyed door lock
- Magnetic door gasket for positive seal
- Heavy duty door handle
- Leveling legs
- One probe access port (3/4")
- White textured cabinet and door
- High density urethane foam cabinet and door insulation
- Natural, Hydrocarbon Refrigerant (R600a)
- One (1) year parts and labor warranty, plus additional Four (4) year compressor parts warranty

Specifications

- Exterior dimensions: 23625" W x 24"D x 73"H
- Cycle defrost
- 115V, 60 Hz, 2.5 Amps, 1/5 HP
- ETL listed
- Shipping weight: 200 lbs.

Temp Controller

- Microprocessor Temperature Controller
- Adjustable operating temperature range: 1°-10°C
- Digital Temperature Display
- Sample simulated digital temperature display; .1° Resolution
- Audible and visual high/low temperature alarms
- Remote alarm contacts