



## Description:



Replaces Part # LRP-LB-26

The Basic Series Glass Door Laboratory Refrigerators are purpose built for scientific and medical applications. These units feature a digital microprocessor temperature controller allowing for the precise temperature management necessary for critical samples and supplies. A forced air directional refrigeration system provides superior temperature uniformity and recovery after door openings.

The all-new temperature display and alarm module offers product security with a monitoring and alarm system. Real-time sample simulated temperatures are constantly displayed and supported by audible/visual high and low temperature alarms.

**Environmentally friendly, natural hydrocarbon (HC) refrigerants (not containing hydrofluorocarbons) vastly reduce global-warming potential (GWP) while meeting new EPA/SNAP mandates and UL, ASHRAE compliance guidelines**

## Additional Product Images



## Details

- 26 Cu. Ft. Capacity
- One swing glass door, self-closing (energy efficient, double pane vacuum insulated), right hinged, not reversible
- Four adjustable shelves (adjustable in ½" increments)
- Forced draft air circulation
- Keyed door lock
- Magnetic door gasket for positive seal
- Heavy duty door handle
- Swivel Casters (3 ½")
- LED interior lights are safety shielded and switch controlled
- Hydrocarbon, natural refrigerant (R290)
- One year parts and labor warranty, plus an additional four year compressor parts warranty

## Specifications

- Exterior dimensions:
  - Width: 28 ½"
  - Depth: 36 ½"
  - Height: 81 ¾" with casters; 78 ¼" without casters
- Cycle defrost
- 115V, 60 Hz, 3 Amps, 1/5 HP
- ETL listed
- ENERGY STAR CERTIFIED
- Shipping weight: 355 lbs.

## Temp Controller

- Microprocessor temperature controller
- Digital temperature display
- Audible and visual high and low temperature alarms
- 2 probes; 1 in air and 1 in sample bottle
- Remote alarm contacts
- Adjustable operating temperature: 1°C to 10°C