



### Description:



The Plus Series Pharmacy/Vaccine Freestanding Undercounter Refrigerators feature a microprocessor temperature controller and display. An interior fan driven, forced-draft air circulation system provides excellent temperature uniformity and recovery after door openings. Critical samples and supplies are security backed with an extensive package of audible and visual alarms. **The Freestanding models (“UCFS”) require 4” of clearance around back and sides of the unit for proper ventilation. Improper installation will void the warranty and will lead to temperature maintenance issues, overheating and possible failure. Note: This unit must have 4” clearance on sides and back for adequate ventilation Lab Research Products is Going Green!** We are an industry leader in providing a variety of Refrigerators and Freezers that are built with Hydrocarbon Refrigerants, R290 or R600a. **Environmentally friendly, natural hydrocarbon (HC) refrigerants (not containing hydrofluorocarbons) vastly reduce global-warming potential (GWP) while meeting new EPA/SNAP mandates and UL, ASHRAE compliance guidelines.**

### Additional Product Images



### Details

- Three adjustable shelves with guard rail on back to prevent product from being pushed against the back wall
- Bottom footed shelf to allow air circulation
- Back wall evaporator cover
- Forced draft circulation
- Vaccine storage power cord warning label
- Keyed door lock
- Magnetic door gasket for positive seal
- Leveling legs
- LED interior light
- Switch activated light
- HFC-free refrigerant (R600a), foam insulation and packaging
- Pharmacy refrigerator/freezer toolkit and temperature logs
- Pyxis®, Omnicell® and AcuDose RX® compatible

- Two year parts and labor warranty, plus an additional three year compressor parts only warranty
- Model: PH-LRP-HC-UCFS-0504G

## Specifications

- Exterior dimensions: Width: 23 3/4" Depth: 24" Height: 32 1/8"
- Cycle defrost
- 115V, 60 Hz, 1.3 Amps, 1/6 HP
- ENERGY STAR CERTIFIED
- Energy Consumption 1.15 kWh/day
- UL/C-UL listed
- Shipping weight: 129 lbs.

## Temp Controller

- Microprocessor temperature controller
- Digital temperature display
- 2 probes; 1 in air and 1 in glycol bottle
- Adjustable operating temperature range: 36°F – 46°F (2°C – 8°C)
- Calibrated using a NIST traceable device, certificate included
- Audible and visual high and low temperature alarms
- Remote alarm contacts