

Product Name:	LRP-HC-72
Description:	<p>Plus Series Glass Door Laboratory Refrigerator  72 Cu. Ft. capacity  Three swing glass doors, self-closing (energy efficient, double pane vacuum insulated)  Microprocessor Temperature Controller  Adjustable operating temperature range: 1°-10°C  Standard Digital Temperature Display and Alarm Module with battery back-up to support temperature monitoring and alarms  Sample simulated digital temperature display; .1° Resolution  Adjustable temperature display in Celsius or Fahrenheit  Audible and visual high/low temperature alarms  Sensor error alarm  Power failure alarm  Resettable 1-point Min/Max History  Remote alarm contacts  Alarm validation (audible, visual, and remote alarm)  Alarm mute with ring back  Twelve adjustable shelves (adjustable in ½" increments)  Forced draft air circulation  Keyed door lock  Magnetic door gasket for positive seal  Heavy duty door handles  LED interior lights are safety shielded and switch controlled  Swivel casters (adds 4" to height)  Probe access port (3/8")  White laminated vinyl exterior  White aluminum liner and stainless steel floor interior  HFC-free refrigerant (R290), foam insulation and packaging  Two year parts and labor warranty, plus an additional three year compressor parts warranty  Exterior dimensions: 78 1/4" W x 31" D x 82 5/8" H with casters; 78 5/8" H without casters  Cycle defrost  115V, 60 Hz, 8.5 Amps, 1/2 HP, BTU/HR 7315  UL/C-UL listed  ENERGY STAR CERTIFIED  Shipping weight: 690 lbs.</p>