

Product Name:	LRP-HC-CB-33
Description:	<p>Basic Series Glass Door Chromatography Refrigerator 33 Cu. Ft. Capacity Two sliding glass doors, self-closing (energy efficient, double pane vacuum insulated) Microprocessor temperature controller Digital temperature display Audible and visual high and low temperature alarms 2 probes; 1 in air and 1 in sample bottle Remote alarm contacts Adjustable operating temperature: 1°C to 10°C Eight adjustable shelves (adjustable in ½" increments) Forced draft air circulation Keyed door lock Magnetic door gasket for positive seal Integrated door handles Swivel Casters (3 ½") LED interior lights are safety shielded and switch controlled One GFCI protected duplex electrical outlet One 2" access port with spring loaded self-closing, gasketed metal cover Probe access port (¾") Powder coated steel white interior and exterior High density urethane foam cabinet insulation Hydrocarbon, natural refrigerant (R290) One year parts and labor warranty, plus an additional four year compressor parts warranty Exterior dimensions: 40 ⅜" W* x 33 ¼" D x 81 ¾" H with casters; 78 ¼" H without casters. *Width with access port closed; 44 ⅜" width with access port open Cycle defrost 115V, 60 Hz, 4.5 Amps, 1/4 HP ETL listed Shipping weight: 419 lbs. Note: This unit requires two (2) outlets</p>