

Product Name:	LRP-HC-CP-47
Description:	<p>Plus Series Glass Door Chromatography Refrigerator 47 Cu. Ft. capacity Two sliding glass doors, self-closing (energy efficient, double pane vacuum insulated) Microprocessor Temperature Controller Adjustable operating temperature range: 1°-10°C Digital Temperature Display and Alarm Module Sample simulated digital temperature display; .1° Resolution 2 probes; 1 in air and 1 in sample bottle Adjustable temperature display in Celsius or Fahrenheit Audible and visual high/low temperature alarms Sensor error alarm; Power failure alarm Resettable 1-point Min/Max History Remote alarm contacts Alarm validation (audible, visual, and remote alarm) Alarm mute with ring back Eight adjustable shelves (adjustable in ½" increments) Forced draft air circulation Keyed door lock One GFCI protected duplex electrical outlet Two 2" access ports with spring-loaded, self-closing gasketed metal covers Magnetic door gasket for positive seal and integrated door handles LED interior lights are safety shielded and switch controlled Swivel Casters (3 ½") Probe access port (3/4") Advanced hydrocarbon detector White powder-coated steel exterior and interior High density urethane foam cabinet insulation Hydrocarbon, natural refrigerant (R290) Two year parts and labor warranty, plus an additional three compressor parts warranty Exterior dimensions: 55 5/8" W* x 33 1/4" D x 81 3/4" H with casters; 78 1/4" H without casters. *Width w/access ports closed;63 5/8" width w/access ports open Cycle defrost 115V, 60 Hz, 4.5 Amps, 1/4 HP ETL listed Shipping weight: 508 lbs. Note: This unit requires two (2) outlets</p>