

|               |  |
|---------------|--|
| Product Name: | LRP-HC-LP-26-TS  |
| Description:  | <p>TempLog Plus Series Glass Door Laboratory Refrigerator<br/> 26 Cu. Ft. capacity<br/> One swing glass door, self-closing, right hinged, not reversible<br/> Microprocessor temperature controller<br/> Adjustable operating temperature range: 1°C - 10°C<br/> Touch Screen Digital Temperature Display and Alarm Module<br/> Password-protected control panel<br/> Sample simulated digital temperature display; .1° Resolution, adjustable temperature display in Celsius or Fahrenheit<br/> Active temperature scale bar display<br/> Resettable 1-point min/max history<br/> Digital 24-hour temperature chart<br/> Temperature data logging<br/> USB port for data transfer and software updates<br/> Real-time operational display clock<br/> 4-20mA output<br/> Electronic troubleshooting guide<br/> Electronic QR Code to access Owner's Manual &amp; technical support contact information<br/> Adjustable alarm volume<br/> Audible and visual high/low temperature alarms<br/> 2 probes; 1 in air and 1 in sample bottle<br/> Sensor error alarm<br/> Power failure alarm<br/> Door ajar alarm<br/> Low battery alarm<br/> Operation indicator<br/> Alarm validation (audible, visual, and remote alarm) and alarm mute with ring back<br/> Remote alarm contacts<br/> Four adjustable shelves (adjustable in ½" increments)<br/> Forced draft air circulation<br/> Keyed door lock<br/> Magnetic door gasket for positive seal<br/> Heavy duty door handle<br/> LED interior lights are safety shielded and switch controlled<br/> Swivel casters (3 ½")<br/> probe access port (3/8")<br/> White powder-coated steel exterior and interior<br/> High density urethane foam cabinet insulation<br/> Hydrocarbon, natural refrigerant (R290)<br/> Three year parts and labor warranty, plus an additional two year compressor parts warranty<br/> Exterior dimensions: 28 3/8" W x 36 ½" D x 78 ¼" H without casters; 81 ¾" H with casters<br/> Cycle defrost<br/> 115V, 60 Hz, 3 Amps, 1/5 HP<br/> ENERGY STAR CERTIFIED<br/> ETL listed<br/> Shipping weight: 355 lbs.</p> |