

Product Name:	LRP-HC-LP-33-TS
Description:	<p>TempLog Plus Series Glass Door Laboratory Refrigerator  33 Cu. Ft. capacity  Two sliding glass doors, self-closing (energy efficient, double pane vacuum insulated)  Microprocessor temperature controller  Adjustable operating temperature range: 1°C - 10°C  Touch Screen Digital Temperature Display and Alarm Module  Password-protected control panel  Sample simulated digital temperature display; .1° Resolution, adjustable temperature display in Celsius or Fahrenheit  Active temperature scale bar display  Resettable 1-point min/max history  Digital 24-hour temperature chart  Temperature data logging  USB port for data transfer and software updates  Real-time operational display clock  4-20mA output  Electronic troubleshooting guide  Electronic QR Code to access Owner's Manual &amp; technical support contact Information  Adjustable alarm volume  Audible and visual high/low temperature alarms  2 probes; 1 in air and 1 in sample bottle  Sensor error alarm; Power failure alarm  Door ajar alarm  Low battery alarm  Operation indicator  Alarm validation (audible, visual, and remote alarm) and alarm mute with ring back  Remote alarm contacts  Eight adjustable shelves (adjustable in 1/2" increments)  Forced draft air circulation  Keyed door locks  Magnetic door gasket for positive seal  Integrated door handles  LED interior lights are safety shielded and switch controlled  Swivel Casters (3 1/2")  Probe access port (3/8")  White powder-coated steel exterior and interior  High density urethane foam cabinet insulation  Hydrocarbon, natural refrigerant (R290)  Three year parts and labor warranty, plus an additional two year compressor parts warranty  Exterior dimensions: 39 5/8" W x 33 1/4" D x 81 3/4" H with casters; 78 1/4" H without casters  Cycle defrost  115V, 60 Hz, 4.5 Amps, 1/4 HP  ETL listed  Shipping weight: 419 lbs.</p>