

Product Name:	LRP-HC-LP-72
Description:	<p>Plus Series Glass Door Laboratory Refrigerator 72 Cu. Ft. capacity Three swing glass doors, self-closing, right hinged, not reversible Microprocessor Temperature Controller Adjustable operating temperature range: 1°-10°C Digital Temperature Display and Alarm Module Sample simulated digital temperature display; .1° Resolution Adjustable temperature display in Celsius or Fahrenheit Audible and visual high/low temperature alarms 2 probes; 1 in air and 1 in sample bottle Sensor error alarm Power failure alarm Resettable 1-point Min/Max History Remote alarm contacts Alarm validation (audible, visual, and remote alarm) Alarm mute with ring back Twelve adjustable shelves (adjustable in ½" increments) Forced draft air circulation Keyed door lock Magnetic door gasket for positive seal Heavy duty door handle LED interior lights are safety shielded and switch controlled Swivel casters (3 ½") Probe access port (3/8") White powder-coated steel exterior and interior High density urethane foam cabinet insulation Hydrocarbon, natural refrigerant (R290) Two year parts and labor warranty, plus an additional three year compressor parts warranty Exterior dimensions: 81" W x 34" D x 78 ¼" H without casters; 81 ¾" H with casters Cycle defrost 115V, 60 Hz, 7.5 Amps, 1/2 HP ETL listed Shipping weight: 743 lbs.</p>