

Product Name:	LRP-HCPP-23
Description:	<p>Plus Series Stainless Steel Laboratory Refrigerator 23 Cu. Ft. Capacity One swing stainless steel door Multi-Point temperature mapping via NIST traceable data acquisition, 15 probes in air and 3 probes in sample solution for 360 minutes with temperature readings every 60 seconds Microprocessor Temperature Controller Adjustable operating temperature range: 1°C - 10°C Digital Temperature Display and Alarm Module with battery back-up to support temperature monitoring and alarms Sample simulated digital temperature display; .1° Resolution Adjustable temperature display in Celsius or Fahrenheit Audible and visual high/low temperature alarms Sensor error alarm Power failure alarm Resettable 1-point min/max history Remote alarm contacts Alarm validation (audible, visual, and remote alarm) Alarm mute with ring back Three shelves (adjustable in ½" increments) Forced draft air circulation Keyed door lock Magnetic door gasket for positive seal Heavy duty door handle Swivel casters (adds 5" to height) Interior light Probe access port (3/8") Stainless steel interior/exterior High density urethane foam cabinet insulation HFC-free refrigerant (R290), foam insulation and packaging Two year parts and labor warranty, plus an additional three year compressor parts warranty Exterior dimensions: 27"W x 30 ¾"D x 83 ¼"H with casters; 78 ¼"H without casters Cycle defrost 115V, 60 Hz, 2.2 Amps, 1/4 HP, BTU/HR 4932 UL/C-UL listed Shipping weight: 310 lbs.</p>