

Product Name:	LRP-HCPP-49G
Description:	<p>Plus Series Stainless Steel Laboratory Refrigerator  49 Cu. Ft. Capacity  Two swing glass doors, self-closing (energy efficient, double pane vacuum insulated)  Multi-Point temperature mapping via NIST traceable data acquisition, 15 probes in air and 3 probes in sample solution for 360 minutes with temperature readings every 60 seconds  Microprocessor Temperature Controller  Adjustable operating temperature range: 1°C - 10°C  Digital Temperature Display and Alarm Module with battery back-up to support temperature monitoring and alarms  Sample simulated digital temperature display; .1° Resolution  Adjustable temperature display in Celsius or Fahrenheit  Audible and visual high/low temperature alarms  Sensor error alarm  Power failure alarm  Resettable 1-point min/max history  Remote alarm contacts  Alarm validation (audible, visual, and remote alarm)  Alarm mute with ring back  Six shelves (adjustable in ½" increments)  Forced draft air circulation  Keyed door lock  Magnetic door gasket for positive seal  Heavy duty door handles  Swivel casters adds 5" to height  Interior light  Probe access port (3/8")  Stainless steel interior/exterior  High density urethane foam cabinet insulation  HFC-free refrigerant (R290), foam insulation and packaging  Two year parts and labor warranty, plus an additional three year compressor parts warranty  Exterior dimensions: 54"W x 31 5/8"D x 83 ¼"H with casters;  78 ¼"H without casters  Cycle defrost  115V, 60 Hz, 5.4 Amps, 1/2 HP, BTU/HR 7315  UL/C-UL listed  Shipping weight: 495 lbs.</p>