

Product Name:	LRP-MFP-30
Description:	<p>Plus Series Manual Defrost Laboratory Freezer 30 Cu. Ft. capacity One solid swing door, right hinged, not reversible Five inner "fast-freeze compartments" with doors for temperature maintenance and recovery Microprocessor Temperature Controller Adjustable operating temperature range: -15°-25°C Standard Digital Temperature Display and Alarm Module Sample simulated digital temperature display; .1° Resolution Adjustable temperature display in Celsius or Fahrenheit Audible and visual high/low temperature alarms Sensor error alarm Power failure alarm Resettable 1-point Min/Max History Remote alarm contacts Alarm validation (audible, visual, and remote alarm) Alarm mute with ring back Four fixed shelves Keyed door lock Magnetic door gasket for positive seal Stainless steel door handle Caster platform (adds 4" to height) One probe access port (3/8") White textured cabinet and door High density urethane foam cabinet and door insulation CFC-free refrigerant (R404a), foam insulation and packaging Two year parts and labor warranty; plus additional three year compressor parts warranty Exterior dimensions: 35 ¾"W x 35"D x 82 ½"H with caster platform; 78 ½"H without caster platform Manual defrost 115V, 60 Hz, 6 Amps, 1/3 HP UL/C-UL listed Shipping weight: 492 lbs.</p>