

Product Name:	PH-LRP-HC-UCFS-0204G
Description:	<p>Plus Series Pharmacy/Vaccine Undercounter Refrigerator</p> <p>Freestanding</p> <p>2.5 Cu. Ft. Capacity</p> <p>One glass swing door, right hinged, not reversible</p> <p>Microprocessor temperature controller</p> <p>Temperature monitor device (TMD) complies with the current CDC guidelines, with 3 years certification of calibration, "buffered" probe in the product simulated solution, min/max memory, F/C switchable, field installable, and visual & audible temp alarm</p> <p>Digital temperature display</p> <p>Audible and visual high and low temperature alarms</p> <p>Remote alarm contacts</p> <p>2 probes; 1 in air and 1 in sample bottle</p> <p>Four adjustable shelves (two large, two small) with guard rail on back to prevent product from being pushed against the back wall</p> <p>Back wall evaporator cover</p> <p>Forced draft circulation</p> <p>Vaccine storage power cord warning label</p> <p>Keyed door lock</p> <p>Magnetic door gasket for positive seal</p> <p>Leveling legs</p> <p>LED light</p> <p>Probe access port (3/8")</p> <p>Powder coat exterior</p> <p>High density urethane foam cabinet and door insulation</p> <p>HFC-free refrigerant (R600a), foam insulation and packaging</p> <p>Two year parts and labor warranty, plus an additional three year compressor parts only warranty</p> <p>Pharmacy refrigerator/freezer toolkit and temperature logs</p> <p>Pyxis®, Omnicell® and AcuDose RX® compatible</p> <p>Exterior dimensions: 17 ¾"W x 19 ½"D x 28 ⅞"H</p> <p><i>Note: This unit must have 4" clearance on sides and back for adequate ventilation</i></p> <p>Cycle defrost</p> <p>115V, 60 Hz, .90 Amps, 1/8 HP</p> <p>ENERGY STAR CERTIFIED</p> <p>Energy Consumption 0.58 kWh/day</p> <p>ADA compliant</p> <p>UL/C-UL listed</p> <p>Shipping weight: 97 lbs.</p>